

SCHEUCHERHEAVY USE CERTIFICATE

Transparent coating for wooden floors **ÖNORM C2354**

TENSEO SURFACE ONLY

The floor finishes are divided into 3 classes:

A – moderate stress	B – stronger stress	C – very heavy stress
slight use of street shoes (eg living rooms and bedrooms)	usual use of street shoes (eg. kindergarden and wardrobe areas)	constant use of street shoes (eg school rooms, restaurants, offices, shops and other public premises)



SCHEUCHERHEAVY USE CERTIFICATE TENSEO

SCHEUCHER

TENSEO-UV-LACQUER

HAS HIGHEST RATING

C

Ergebnisse der Untersuchung

Die Beschichtung des Schiffsboden 3-Strip Steirer Eiche select konnte bei den durchgeführten Prüfungen folgende Bewertungsklassen erreichen:

Prüfung	Ergebnisse
Verformbarkeit (Kegel-Bezeichnung) vor Alterung	7,5
Verformbarkeit (Kegel-Bezeichnung) nach Alterung	9,0
Kratzfestigkeit [N]	2,0
Haftvermögen (Gitterschnittkennwert) vor Alterung	0
Haftvermögen (Gitterschnittkennwert) nach Alterung	0
Chemikalienbeständigkeit	1-B

Die geprüfte Oberfläche entspricht den Anforderungen der ÖNORM C 2354 Klasse C „besonders starke Beanspruchung“.

Das Probenmaterial wird mindestens 1 Monat ab Berichtslegung aufbewahrt.

To explain the results:

Deformability: the smaller the number, the higher and better is the ductility, a good deformable paint film does not break if damaged, but follows the deformation.

Scratch resistance: the higher the number, the higher and better the scratch resistance

Adhesiveness: the smaller the number, the higher and better the adhesion of the paint to the wood below

Chemical resistance: 1-B is highest class achievable for coatings

HOLZFORSCHUNG AUSTRIA



DI Dr. G. Grill
Zeichnungsberechtigter und Bearbeiter



DI A. Illy